

Assembly Device Hand Held:



Cat. #: BLT-PAD:

Our Standard Pneumatic Assembly Device or PAD is designed for Retainer assembly on Silicone tubing for BioBags and other flexible fabrication needs.

Use: Hand Held or Bench Mounted

Dimensions: 1-3/4" x 7" x 12"

Air Requirements: Clean Non-Oil / 90 psi Compressed Air

Material: Stainless Steel Frame, Fittings, and Cylinder

Cylinder: 1-3/4" Bimba Single Acting Cylinder

Valves: Thumb Button Valve / Legris Time Over Pressure Valve

Jaw Mounting: Face Mounting Single SS SHCS

Jaw Sizes: 125 through 501 Series Retainer

Note: Jaws must be ordered separately.



Cat. #: BLT-PAD-HD

Our HD Pneumatic Assembly Device or PAD-HD is designed for closure of our 625-Series Retainers and other high durometer tubing closure requirements.

Use: Hand Held or Bench Mounted

Dimensions: 2-1/2" x 7" x 12"

Air Requirements: Clean Non-Oil / 90 psi Compressed Air

Material: Stainless Steel Frame, Fittings, and Cylinder

Cylinder: 2-1/2" Bimba Single Acting Cylinder

Valves: Thumb Button Valve / Legris Time Over Pressure Valve

Jaw Mounting: Face Mounting Single SS SHCS

Jaw Sizes: 125 through 625 Series Retainer

Note: Jaws must be ordered separately.